

SI52-12S

Full HD AI-Powered Network IR Bullet Camera













Superior Image Quality

1/2.8" 2MP CMOS sensor

FHD 1080p 30fps image

Varifocal AF Lens

Storage and bandwith savings with Codec H.265

Ultra low light integrated at 0.002 Lux

High quality color images under low light environments

With 3D noise reduction, auto iris, WDR and HLC

Recognition Functions

Identify multiple targets simultaneously

Target tracking and feature recognition

Bi-directional people counter

Built-in algorithm for image comparison ability

Intelligent Face Detection that detect face and optimizes the exposure optimally

High Performance IR

Industry-standard IR LED with longer life expectancy

Long-range with Smart IR feature

Other Highlights

Expandable memory with MicroSD card

Supports Automatic Network Replenishment (ANR)

Bi-directional audio/ alarm input & output/ RS485 standard

Support multiple streams (up to 3)

PoE enabled



IDvaco Private Limited 627A Aljunied Road #06-02 BizTech Centre, Singapore 389842 www.idvaco.com

TECHNICAL SPECIFICATIONS

| CAMERA | |
|--|---|
| Image Sensor | Progressive scan CMOS 1/2.8" with 2.0 Megapixel Digital Wide Dynamic Range S/N Ratio: >52dB |
| Minimum Illumination | Color: 0.002Lux @ (<i>f</i> /1.2, AGC on) B/W: 0.0002Lux @ (<i>f</i> /1.2, AGC on) |
| Shutter Time | 1 - 1/30,000 secs |
| Day and Night | Automatic infared-cut filter, color, black & white |
| Lens | Mount Type: Φ14 |
| | Auto Iris: DC drive |
| | Focal Length: 7022: auto varifocal, 7 - 22mm, f/1.4 |
| | Focus: manual/ semi-auto/ auto |
| Infrared | IR Distance: 30 - 50m IR Intensity: Smart IR |
| Other Settings | Auto/ Manual White Balance Auto/ Manual Gain Control Backlight Compensation: BLC / HLC / WDR / Off |
| VIDEO | |
| Compression | H.265, H.264, MJPEG |
| Image Resolution and Frame Rate | Main stream: 1080p at 30fps Sub stream: D1 at 30fps |
| Bitrate | 32kbps to 16Mbps |
| Multi-Stream | Supported |
| Image Settings | Bitrate Control: VBR / CBR |
| | Privacy masking & motion detection: up to 4 zones |
| | Video Stamper: timestamp / alert / customize |
| | 3D Noise Reduction, freeze frame, rotating image, mirroring of image |
| AUDIO | |
| Audio Capability | Compression: G.711a / G.711u / ADPCM / G.722 / AAC-LC / G.722.1c/ G.726 |
| | |
| | Bitrate: 32kbps - 64kbps |

| NETWORK | |
|--|---|
| Supported Protocols | IPv4, IPv6, TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, VSIP, UPnP, 802.1x, NAT, QoS, SMTP |
| User Interface | Web control works with IE, Firefox and Chrome |
| Max. User Access | 10 users |
| Compability | Onvif (Profile S/G), API, CGI |
| Automatic Network Replenishment (ANR) | Supported |
| INTELLIGENT F | UNCTIONS |
| Detection and Tracking | Face detection and recognition for up to 18 targets simultaneously |
| Image Capturing | Person, Face, Full view |
| Coptaining | Built-in algorithm for image comparison ability, select best shot automatically |
| Detectors | Direction detector, speed detector |
| People Counter | Bi-directional counting |
| Photo Enhancement | Intelligenc face detection |
| CONNECTORS | |
| Network Connectivity | RJ-45 connector, 10/100M |
| Control | 1 x RS485 |
| Audio In / Out | 1 x Input, 1 x Output |
| Alarm In / Out | 1 x Input, 1 x Output |
| External Memory | Support up to 128GB MicroSD card |
| ALERT AND NO | TIFICATIONS |
| Condition Triggers | Input alarm / network disconnection / low disk space / disk read error |
| Event Triggers | Alarm incident report / recording / text overlay / snapshot / external output / email notification / acoustic alarm |
| GENERAL | |
| Operating Conditions | Temperature: -40°C ~ 40°C (-40 °F ~ 104 °F) |
| oonuluons | Humidity 10% to 95% |
| Power | AC 24V ± 10%, DC12V ± 10%, PoE (IEEE802.3at), Max. 20W |
| Weight | 1 kg/ 2.2lb (GWT) |
| Dimensions | 181.5 x 80 x 73mm / 7.15" x 3.15" x 2.87" |



IDvaco Private Limited
627A Aljunied Road #06-02
BizTech Centre, Singapore 389842