

FDH40S universal mounting unbreakable fire door holding electromagnets



Standard, floor mounted. Wall to door distance: 114mm.



Standard, floor mounted. Wall to door distance: 153mm.



Wall mounted, 126mm extn. tube.
Overall: 202mm (incl. armature).



Wall mounted, 156mm extn. tube.
Overall: 232mm (incl. armature).



Wall mounted, 355mm extn. tube.
Overall: 431mm (incl. armature).

- 10 year guarantee*
- Low power consumption for lower operating temperature
- Total flexibility - one product suits floor and wall mounting
- Universal armature - offsets to 55° to suit doors opening past 90°
- Additional flexible mounting in both planes to speed alignment
- Wall mount extensions available
- Wall mounted, overall 431mm, is also available finished switch end only, and can be cut to any length
- 12 VDC models - red wires; 24 VDC models - blue wires
- Push off button means no residual magnetism
- Oversize armature for easy alignment
- Emergency release button
- Blackened stainless steel screws for aesthetic appeal
- All stainless steel fittings
- Electroless nickel plated armature and electromagnet for maximum durability and aesthetic appeal
- Designed, tested and produced in New Zealand to AS 4178
- Full local support and back up

FDH40SS stainless steel surface & flush mounting

fire door holding electromagnets

